

CERES RACK Li Series

1~3kVA online Rack UPS

Power range

Operation

1~3kVA

Applications

1P/1P, online double conversion

Characteristics

- Government, Finance, IT, Education, Transportation,
- Broadcasting, Medical,
- Energy, etc.
- High efficiency up to 95.5%.
- Output PF=1, high load adaptability.
- Wide input voltage range of 110~300Vac.
- Max charging current up to 12A.

Model		CERES SRLi-1K	CERES SRKLi-1K	CERES SRLi-2K	CERES SRKLi-2K	CERES SRLi-3K	CERES SRKLi-3K
Rate Power		1kVA/1kW	1kVA/1kW	2kVA/2kW	2kVA/2kW	3kVA/3kW	3kVA/3kW
Cold start		Default output 50/60Hz					
Input voltage range		110~300VAC;100% load@176VAC~276VAC, 100%~50% power derating@110VAC~176VAC, 50% load@276VAC~300VAC					
Input power factor		≥0.99					
Frequency range		50/60±5Hz(default),±3Hz/±10Hz(settable)					
Output power factor		1.0					
Output	Rate voltage	208VAC/220VAC/230VAC/240VAC					
	Load response	≤5% (0% - 100% -0% step load)					
	Recovery time	≤40ms (0% - 100% -0% step load)					
	Output THDu	≤2% , Linear load ; ≤ 5% non-linear load according to IEC62040-3					
Transfer time	Main to BAT	0					
	INV to BYP	4ms					
Efficiency (normal mode)		95.0% 95.5%					
Noise (1 meter)		45dB@>70% loa	ad or >6A charge	50dB@>70% load or >6A charge 50dB@>70% load or >6A charge			
	Normal	102%~110%: 30mins, 110%~125%:10mins, 125%~150%: 30 seconds					
Overload	Battery mode	102%~110%: 1min, 110%~125%: 10 seconds, 125%~150%:5 seconds					
	Bypass mode	<130%: long time, 130%~150%:10mins, 150%~180%:5 seconds					
Battery	Model	12.8VDC/9Ah	50Ah/100Ah	12.8VDC/9Ah	50Ah/100Ah	12.8VDC/9Ah	50Ah/100Ah
			Depend on		Depend on		Depend on
	Quantity	2/3	external battery	4/6	external battery	6	external battery
	Max charging	1-4A(settable)	1-12A(settable)	1-4A(settable)	1-12A(settable)	1-4A(settable)	1-12A(settable)
	Rate voltage	25.6VDC/38.4VDC		51.2VDC/76.8VDC		76.8VDC/102.4VDC	
	Standard	EPO, RS232					
Option		SNMP card, AS400, USB, RS485, BMS by dry contact, Air filter					
Dimension ,W*D*H(mm)		440*440*86		440*580*86		440*580*86	
	Weight (kg)	15.5/16.8	9.5	20.7/23.3	9.7	23.8	10

Statement: The products will continue to be innovative and optimized, which may lead to asynchronized updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.